CR

25X1

25X1

25X1

## INFORMATION REPORT INFORMATION REPORT

## CENTRAL INTELLIGENCE AGENCY

New Soviet Motorized Pile Driver DA' or Tamper  NO REG				CING U	Or a	25X
A new motorized pile driver or tamper (Ramme) observed in East Germany is described as followed as front axle motor axle motor operator's cab Height about 2. front heavily ram  Comment. A device of this type has not parts of a device which is structural.			CFZ	SING C	•	∠ɔ <i>X</i>
A new motorized pile driver or tamper (Ramme) observed in East Germany is described as follows front axle rear axle single-wheeled, at the rear of operator's cab Height about 2. front heavily ram  Comment. A device of this type has not provided the structural of t	REPORT					
A new motorized pile driver or tamper (Ramme) observed in East Germany is described as follows front axle the rear axle single-wheeled, at the rear of operator's cab theight about 2. front heavily ram  Comment. A device of this type has not processors.	DATE DISTR.	STR.	M Apr	i1 <sub>8,1</sub>	957.	
SOURCE EVALUATIONS ARE DEFINITIVE. APPRAISAL  A new motorized pile driver or tamper (Ramme) observed in East Germany is described as followed by the front axle and the rear axle single-wheeled, at the rear of operator's cab theight about 2.0 front heavily ram  Comment. A device of this type has not provided by the structural about 3.5 m.	NO. PAGES	ES	1			
SOURCE EVALUATIONS ARE DEFINITIVE. APPRAISAL  A new motorized pile driver or tamper (Ramme) observed in East Germany is described as followed by the front axle and the rear axle and the rear of the properator's cab and the rear of th	REQUIREMEN NO.	<b>MENT</b>	RD			
SOURCE EVALUATIONS ARE DEFINITIVE. APPRAISAL  A new motorized pile driver or tamper (Ramme) observed in East Germany is described as followed by the front axle axle axle axle axle axle axle axle	REFERENCES	CES				
SOURCE EVALUATIONS ARE DEFINITIVE. APPRAISAL  A new motorized pile driver or tamper (Ramme) observed in East Germany is described as followed by the front axle and the street axle are supported by the street axle are supported by the street axis.  Twin wheels with single-wheeled, at the rear of the support about 2.5 front heavily ram front of the with a rammer rear, presumal about 3.5 m.  Comment. A device of this type has not provided by the structural axis.						25>
A new motorized pile driver or tamper (Ramme) observed in East Germany is described as followed by the front axle and the rear axle and the rear of the properator's cab argument. A device of this type has not properator. A device of this type has not properator of a device which is structural.						25)
_the existence of a device which is structural]	of the web	rcer t	nan the	iront	exte	
	2.5 meter ily glasse the operat mer; track umably adj	ters fi sed i etori cks s djust	rom the n s cab, 2 lightly able; le	2 vertice incline ength of	eal to	the
SECRET	2.5 meter ily glasse the operat mer; track umably adj	ters fi sed i setor! icks si idjust	rom the n s cab, 2 lightly able; le	2 vertice incline ength of	eal to	the k
	2.5 meter ily glasse the operat mer; track umably adj	ters fi sed i setor! icks si idjust	rom the n s cab, 2 lightly able; le	2 vertice incline ength of	eal to	the

Sanitized Copy Approved for Release 2010/03/05 : CIA-RDP80T00246A033800100001-5

Sanitized Copy Approved for Release 2010/03/05 : CIA-RDP80T00246A033800100001-5

25X1

